



Components

1	Body	Cast iron or Ductile iron
2	Plug	Cast iron or Ductile iron
3	Cover	Cast iron or Ductile iron
4	Screen	stainless steel
5	Bolt	Carbon steel

Application

1	Face to face is according to DIN3202-F1
2	Flange drilled is according to DIN2531/2532/2533

Test

Working pressure	PN10	PN16
Shell pressure	1.5MPa	2.4MPa
Seat pressure	1.1MPa	1.76MPa

Dimensions

	unit:mm									
DN	40	50	65	80	100	125	150	200	250	300
L	200	230	290	310	350	400	480	600	730	850
H	105	125	150	175	195	235	275	350	420	490
D (PN10)	150	165	185	200	220	250	285	340	395	445
D (PN16)	150	165	185	200	220	250	285	340	405	460

arco valves pvt. ltd.

DRAWN BY :	Plot No. 23/24 , CIDCO INDUSTRIAL ESTATE,		
CHK. BY :	SECTOR 1-A, AIROLI NAVI-MUMBAI - 400 708		
APPD. BY :	TEL : (022) 27797897 / 98		
DATE :	TITLE : Y -T ypes Strainer		
SCALE : N.T.S			
MAT. : As shown	DRG NO: AVPL	SHEET :1 OF 1	
		REVISION :	